

**CECCHI**

RECTANGULAR



Rectangular bulkhead lamp made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Suitable for wall and ceiling installation. Supplied as option with coloured backlit base. **Kelvin settable GX53 LED** or **E27** version available. Insulation class II, Protection rating IP66.



*Plafoniera rettangolare realizzata in resina antiurto stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Idonea per il montaggio a parete e a soffitto. Disponibile anche con base per retroilluminazione colorata. Fornita nella versione a **LED GX53 con Kelvin impostabile** o **E27**. Classe di isolamento II, grado di protezione IP66.*

1H3.000.CL1



**CCT SETTABLE**

2700 K 4000 K 6500 K

SDCM <6




**CECCHI COMPONENTS**

IP 66



**COVER** made of shockproof resin material, UV-rays stabilized.

**COVER** in resina antiurto stabilizzata ai raggi UV.

Opal **DIFFUSER** made of UV-rays stabilized polymethylmethacrylate (PMMA), with silicone rubber gasket to ensure high protection against external agents.

**DIFFUSORE** opale realizzato in polimetilmetacrilato (PMMA) stabilizzato ai raggi UV. Completo di guarnizione in gomma siliconica per garantire un alto livello di protezione contro gli agenti esterni.

**BASE** made of shockproof resin material, provided with E27 or GX53 lampholder. Available in different backlight colours to create a coloured effect on wall and ceilings.

**BASE** realizzata in resina antiurto. Fornita completa di portalampada E27 o GX53. Disponibile in diversi colori per creare una retroilluminazione colorata su pareti e soffitti.



**CECCHI**



**Dimensions and weight**

Width: 338 mm  
Height: 245 mm  
Depth: 90 mm  
Weight: 1 Kg

**Moulded colours:**

Black  White  Grey

**Diffuser PMMA:**

Opal

**LED LAMPS**



Comply with: EU2019/2015  
EU2019/2020  
Technical details on page 596.

**GX53 LED**



Bulkhead supplied **fully pre-wired** and complete with TÜV-CB certified, long-life, efficient and **Kelvin settable GX53 LED lamp included**. Different wattage available.

- **COST SAVING:** long-life and efficient LED light sources
- **BUILT-IN DRIVER:** Quick and easy lamp replacement for a very simple maintenance after installation.

**100 - 240 V**

LAMP	POWER	LUMINOUS FLUX (Φ TOTAL) UP TO	COLOUR TEMP.	*ADD. SUFFIX
	7,2 W	920 lm	6500 K	.A1K
			4000 K	
			2700 K	
11,3 W	1510 lm	6500 K	.B1K	
		4000 K		
		2700 K		
17 W	2350 lm	6500 K	.E1K	
		4000 K		
		2700 K		

**7,2W**  
**11,3W**  
**17W**

=

**60W**  
**100W**  
**150W**

incandescent

**SAVE 88%**

**E27**




Bulkhead supplied **fully pre-wired** with **E27 lampholder**. White resin reflective plate designed to grant lampholder protection and isolation. Safe fixation of the electrical devices on the plate rear side.

*Daylight and motion sensor* available as an option. Sensor operating voltage: 220-240V (120V available on demand).

<b>E27</b> (CFL -LED)	max 160 mm	.E27
<b>E27 + SENSOR</b> (CFL -LED)		.ES7

**CCT SETTABLE LED LAMP**



CCT switch settable in three different positions, to select the desired Kelvin temperature (2700K/4000K/6500K) and get a customized ambiance.

\* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE





CECCHI GX53	
<b>7,2W</b>	1H3.000.A1K
<b>11,3W</b>	1H3.000.B1K
<b>17W</b>	1H3.000.E1K

CCT SETTABLE GX53 LED LAMP INCLUDED  
2700K/4000K/6500K

Pcs 16  
Kg 18,7  
mc 0,194

CECCHI E27	
<b>E27 lampholder</b>	1H3.000.E27
<b>E27 with sensor</b>	1H3.000.ES7

Pcs 16  
Kg 15,5  
mc 0,194